

TOOLS & MATERIALS REQUIRED



Optional	Tools	Use	Product/Specification
Yes	Brick saw	Perfect straight cuts	Contemporary & Dressed edge
	9" or 4" grinder with concrete cutting blade (diamond blade)	Cutting stone	All Products
	12mm Notched trowel	Buttering tile adhesive onto wall and stone	All products
	Buckets x 2	Mixing tile glue & wash up water	All Products
	Sponge	Wiping excess glue off stones	All Products
Yes	Paint brush	For priming surface	Depends on surface
Yes	Step ladder or scaffolding	Applying stone at height	
	Spirit level and pencil	Gain horizontal levels every 300mm	Not needed for South Coast and Arctic collections
	Tape Measure	Measure cuts when finishing off edge or top of wall	
Yes	Drill with mixing attachment	Mixing tile adhesive	Some adhesives require mechanical mixing.
	Tile wedges	Level up individual stones	All products
Yes	Hammer & Chisel	Splitting stones to gain rough edge cut	Depends on finished look
Yes	Rubber Gloves	Keep hands clean	
Yes	Extension cord	Allow cutting next to installation area	
Yes	Wheel barrow	Moving stones large distance, mixing large amounts of glue	

Tools required for mortar joints

Yes	Small brush	Brushing mortar once firm	
	Piping gun or piping bag	Piping tile grout or mortar between joints	
Yes	Sponge	Wiping mortar once firm	

Materials Needed

	Tile adhesive	Glue stone to wall	All Products
Yes	Surface primer	Depending on glue specifications and substrate	All products
	Pointing mortar mix or Tile grout	Grout the joints.	Tint colour of mortar by adding oxide

Please note: extra materials may be needed if mechanical fixing is required. In some cases an engineer's report may be needed to ensure correct installation practice. The tools and materials recommended are a guide only. If in doubt please seek help from a professional tradesperson or your local Veneer Stone stockist.

Joint: Pointing mortar or tile grout can be used to fill the joints. One of the easiest & fastest ways to fill the joints is with a piping bag. Purchase your silicon piping bag from Veneer Stone by calling 1300 984 572 or email info@veneerstone.com.au

To retain the original fresh quarried look we suggest sealing the stone. If you would like the stone to mellow slightly and gain the European look after years of harsh weathering don't seal the product.

For more information visit our website at www.veneerstone.com.au or call us on 1300 984 572